



Clamp-on Leakage Current Meter Model 565 (Discontinued replaced by Cat.#2139.83)

Economical

Cat. #2117.56

TRMS, 60mA, 600mA, 10A, 100A, 600V AC/DC, Leakage Current Measurement

Measures low AC currents such as leakage currents in ground conductors. Low currents are measured using either the 60mA or 600mA range. The high sensitivity of the probe (10μA and 100μA) is possible through special jaw construction such as critical shielding of the jaws. Can be used as a standard clamp-on meter measuring to 100A RMS, Also measures AC and DC voltage, continuity (with beeper), and resistance.

Cat.#2117.56

Voltage Range:	600Vrms AC/DC Auto-Ranging
Resolution Max:	0.1V
Current Range:	100Arms AC
Resolution Max:	10μA
Accuracy V Typical:	1.0% ± 5cts
Accuracy A Typical:	1.2% ± 5cts
Continuity:	<35Ω
Resistance:	1kΩ
Frequency:	1kHz in V, A
ΔREL:	Yes
Power Source:	2 x AAA, IEC LR03
Battery Life:	45 hrs
Dimensions:	8.5 x 2.5 x 1.18" (218 x 64 x 30mm)
Weight:	10.0 oz. (280g) with batteries
Jaw Opening:	1.10" (28mm)
Operating Temperature:	+32° to 104°F (0° to +40°C)
Storage Temperature:	+14° to 140°F (-10° to +60°C)
Operating Humidity:	80% up to 104°F (40°C)
Pollution Degree:	2

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com