



Clamp-on Meter Model 601

Large Size, Professional Functionality

Cat. #2139.30

TRMS, True InRush[®], 1000V_{AC/DC}, 2000A_{AC}

Measures voltage, current, frequency, resistance, continuity, True InRush[®], and temperature. Performs diode checks. Performs data recording. Safety rated at 1000V CAT IV. IP54 rated to withstand dust and water spray.

Voltage Range:	1000Vrms AC/DC Autoranging
Resolution Max:	0.01V
Current Range:	2000Arms AC
Resolution Max:	0.01A
Accuracy V Typical:	1% ± 3cts
Accuracy A Typical:	1% ± 3cts
True InRush [®] :	10 to 1000A
Continuity:	Selectable from 0 to 999.9Ω
Resistance:	100kΩ
Diode Test:	0 to 3.1999VDC
Frequency:	20kHz in V, 2kHz in A
Temperature K Thermocouple:	-76.0 to 2192°F (-60 to 1200°C)
MIN/MAX:	Yes
Power Source:	4 x AA, NEDA 15A, IEC LR6
Battery Life:	>350 hours
Dimensions:	11.65 x 4.37 x 1.61" (296 x 111 x 41mm)
Weight:	1.4 lbs (640g) with batteries
Jaw Opening:	2.36" (60mm)
Operating Temperature:	-4° to +131°F (-20° to +55°C)
Storage Temperature:	-40° to +158°F (-40° to +70°C)
Operating Humidity:	90% up to 131°F (55°C)
Pollution Degree:	2
Ingress Protection:	IP54

For more details, download the datasheet or user manual at www.aemc.com

EMC:	EN61326-1	
Safety Compliance:	EN/IEC 61010-1 to 1000V CAT IV EN/IEC 61010-2-030:2010 EN/IEC 61010-032:2002	CE

For more details, download the datasheet or user manual at www.aemc.com



15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com