


Summary Sheet




Clamp-on Meter Model 670

Large Size, Professional Functionality
Cat. #2117.49
Dual Display, Auto-Ranging, TRMS
Cat.#2117.49

Voltage Range:	1000V ACrms, 1400V DC Auto-Ranging
Resolution Max:	0.1V
Current Range:	1000Arms AC
Resolution Max:	0.01A
Accuracy V Typical:	1.0% ± 5cts
Accuracy A Typical:	1.5% ± 5cts
Continuity:	<35Ω
Resistance:	10kΩ
Diode:	Yes
Frequency:	10kHz in V, 1kHz in A
Temperature:	Yes
MIN/MAX/PEAK-/PEAK+	Yes
Power Source:	1 x 9V, IEC 6LR61
Battery Life:	35 hours
Dimensions:	10.71 x 3.15 x 1.69" (272 x 80 x 43mm)
Weight:	17 oz. (480g) with battery
Jaw Opening:	1.65" (42mm)

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com



Operating Temperature:	-14° to +122°F (-25 to +50°C)
Storage Temperature:	-14° to +140°F (-25 to +60°C)
Operating Humidity:	80% up to 122°F (50°C)
Pollution Degree:	2
Ingress Protection:	IP30
Safety Compliance:	EN/IEC 61010 to 1000V CAT III

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

