



AC/DC Current Probe Model E94 (Used only with model 8345)

Cat. #2140.82

AC/DC Current Probe Model E94 used only with model 8345

Cat.#2140.82

Clamping Diameter	0.464 in (11.8 mm)
Current Range	100 mA 100 A
Selectable Frequency Ranges	10 A (0.1 to 10) A peak and 100 A (0.5 to 100) A peak)
Dimensions (H x W x D)	(9.09 x 1.41 x 2.65) in (231 x 36 x 67) mm
Weight	11.64 oz (330 g)
Lead length	10 ft (3 m)
Type of current sensor	Type A
Operating Temperature	(14 to 131) °F (-10 to 55) °C
Storage Temperature	(-40 to 158) °F (-40 to 70) °C
Operating Humidity	(10 to 85) % RH
Storage Humidity	(10 to 90) % RH
Double Insulated	Yes
Ingress Protection (Ip)	IP20
Pollution Degree	2
Electromagnetic Compatibility (EMC)	EN/IEC 61326-1
Safety Compliance	EN/IEC 61010-2-032 600 V CAT III, 300 V CAT IV



For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com