



AC Current Probe Model SR604

Cat. #2113.44

1000A, 1mA/A, Lead

General purpose 1000A_{AC} current probe designed for digital multimeters, loggers, and other instruments with current input. Includes integral 5' (1.5m) lead terminated with shrouded banana plugs. Designed for power applications where high accuracy and low phase shift is important.

Cat.#2113.44

Maximum Conductor Size	2.05" (52mm)
Current Range	1000Arms AC
Measurement Range	1 to 1200A
Output	5 ft (1.5m) lead with safety 4mm banana plug
Transformation Ratio	1000:1
Output Signal	1mA/AAC (1A @ 1000A)
Accuracy 50/60Hz	0.5% @ 1000A
Frequency Range	30Hz to 5KHz with current derating
Phase Shift at 50Hz	0.5° @ 1000A
Open Secondary Voltage	Limited to <25V
Load Impedance	1Ω, 5Ω max with derating
Overload	1200A for 40 mn ON then 20 mn OFF
Dimensions (H x W x D)	4.37 x 8.50 x 1.77" (111 x 216 x 45mm)
Weight	1.21 lb (550g)
Operating Temperature	14° to +122°F (-10° to +50°C)
Storage Temperature	-4° to +158°F (-20° to +70°C)
Operating Humidity	90% RH
Pollution Degree	2
Ingress Protection (Ip)	IP40
EMC	EN 61326-1

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com

customerservice@aemc.com • techsupport@aemc.com

Safety Compliance

EN/IEC 61010-1 600V CAT III,
EN/IEC 61010-032



For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

