



## Megohmmeter Model 1050 (Discontinued. See replacement: Model 1060 Cat#2130.03)

Cat. #2130.01

(Discontinued. See replacement:  
)

Cat.#2130.01

AC/DC Voltage Measurement	
Range	1 to 1000V
Accuracy	$\pm(1\% R + 3V)$
Resolution	1 to 99.9V: 0.1V 100 to 1000V: 1V
Frequency Range	DC and 16 to 65Hz
Input Impedance	750k $\Omega$ approx.
Insulation Measurement	
Test Voltage / Resistance Range	50V: 2k $\Omega$ to 200G $\Omega$ 100V: 4k $\Omega$ to 400G $\Omega$ 250V: 10k $\Omega$ to 1T $\Omega$ 500V: 20k $\Omega$ to 2T $\Omega$ 1000V: 40k $\Omega$ to 4T $\Omega$
Measurement Accuracy	2k $\Omega$ to 39.99G $\Omega$ : $\pm(5\%R + 3ct)$ 40.0G $\Omega$ 4T $\Omega$ : $\pm(15\%R + 10ct)$
Auto Discharge	Discharge time < 2s/ $\mu$ F from Vtest to 25V
Live Circuit Indicator	Inhibit test if terminal voltage > 25V prior to initialization of test
Resistance Measurement	
Range	0.01 $\Omega$ to 399.9k $\Omega$
Accuracy	$\pm (3\%R + 3ct)$ at >4k $\Omega$
Open Circuit Voltage	Approximately 12.4V DC
Short Circuit Current	<6mA DC
Continuity Measurement	
Range	0.01 to 39.99 $\Omega$

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

Accuracy	± (3%R + 4ct) with lead compensation
Open Circuit Voltage	12.4V DC
Short Circuit Current	≥ 200mA DC from 0.01 to 20.00Ω
<b>General Features</b>	
Programmable Alarm	Yes
DAR – PI	Yes
Ramp Mode	No
Step Mode	No
Capacitance Measurement	0.05nf to 4.999μf, Accuracy: ± (10%R + 1ct)
Memory	20 Readings
Power Supply	Eight 1.5V C cell batteries (included)
Battery Life	≥ 21000 IR tests at 1000V into 1MΩ with a duty cycle of 5s on and 20s off; ≥ 16,000 R tests of 1Ω with a duty cycle of 5s on and 20s off
Charging Time	4.5 hours approximately
Dimensions	9.45 x 7.28 x 4.33" (240 x 185 x 110mm)
Weight	7.5 lbs (3.4kg)
Altitude Operating	6562' (2000m)
Operating Temperature	14° to +131°F (-10° to +55°C) ≤80% RH
Storage Temperature	-40° to +158°F (-40° to +70°C) ≤90% RH
IP Rating	IP 54
Safety Compliance	EN 61010-1, EN 61557, 600V CAT III, Pollution Degree 2



For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

