



Megohmmeter Model 6527

Cat. #2126.53

Digital 250V, 500V, 1000V, Continuity, 400kΩ, V

Measures insulation resistance from $1k\Omega$ to $4000M\Omega$ using three user selectable test voltages of 250V, 500V, and 1000V. Can perform continuous tests up to 15 minutes. Designed for insulation tests on cables, switchgears, motors, DC generators, power tools, and small appliances. Also functions as a multimeter for measuring voltage, continuity, and other parameters.

Cat.#2126.53

AC/DC Voltage Measurement		
Range	600V AC / 1000V DC	
Accuracy	DC: ±(0.8% R + 3ct) AC: ±(1.2% R + 10ct)	
Resolution	1V	
Frequency Range	DC & 40 to 400Hz	
Input Impedance	10ΜΩ	
Insulation Measurement		
Test Voltage / Resistance Range	250V: $1k\Omega$ to $4G\Omega$ 500V: $1k\Omega$ to $4G\Omega$ 1000V: $1k\Omega$ to $4G\Omega$	
Measurement Accuracy	4MΩ/40MΩ: ±(2% R + 10ct) 400MΩ: ±(3% R + 5ct) 4GΩ: ±(4% R + 5ct)	
Continuity Measurement		
Ranges	0 to 400Ω (≤250mA test current)	
Accuracy	1.2% R + 3ct with lead compensation	
Threshold	Audible signal triggered $<35\Omega\pm3\Omega$	
Resistance Measurement		
Range	400kΩ	
Accuracy	± (1.2%R + 3ct)	
General Features		
DAR – PI	Only DAR	

For more details, download the datasheet or user manual at www.aemc.com



Display	Backlit digital with bargraph
Power Supply	Six AA batteries (NEDA 15A or IEC LR6)
Battery Life	>50h in MΩ, >200h in V AC/DC, >15h in Continuity Test
Dimensions	7.9 x 3.6 x 2.0" (200 x 92 x 50mm)
Weight	24oz (700g)
Altitude Operating	2000m
Operating Temperature	32° to +90°F (0° to +50°C), 90% RH
Storage Temperature	-36° to +126°F (-20° to +70°C), 50% RH
IP Rating	IP 51
Safety Compliance	IEC/EN 61010-1, 600V CAT IV, Pollution Degree

For more details, download the datasheet or user manual at www.aemc.com

