


Summary Sheet



Micro-Ohmmeter Model 6240

Cat. #2129.80

10A, Instantaneous, Continuous, Multiple Test, Manual/Auto Temperature Compensation; includes 10A Kelvin Clips and DataView® software


Four-lead Kelvin tester measures very low resistance from 1μΩ to 400Ω with resolutions to 1μΩ. Selectable test currents of 10A, 1A, 100mA, and 10mA, with a polarity reversal function. Tests both resistive and inductive material, and stores up to 99 measurements. Includes DataView® for configuring the instrument, downloading data, and generating reports.

Cat.#2129.80

Specifications						
Measurement Range	5.0 to 3999 μΩ	4.0 to 39.99 mΩ	40.0 to 399.9 mΩ	400 to 3999 mΩ	4.0 to 39.99 Ω	40.0 to 399.9 Ω
Resolution	1 μΩ	10 μΩ	100 μΩ	1 mΩ	10 mΩ	100 mΩ
Accuracy	±(0.25%R + 2ct)					
Measurement Current	10.2 A ±2%	1.02 A ±2%		102 mA ±2%	10.2 mA ±2%	
Open Voltage	4 to 6V					
Inductance	0.5 H Max					
Voltage Measurement Indication						
Measurement Range	0.01 to 3.999 mV	4 to 39.99 mV	40 to 399.9 mV	0.4 to 3.999 V	4 to 4.70 V	
Resolution	1 μV	10 μV	100 μV	1 mV	10 mV	
Current Measurement Indication						
Measurement Range	5.0 to 39.99 mA	40.0 to 399.9 mA	0.4 to 3.999 A	4 to 11.00 A		
Resolution	10 μA	100 μA	1 mA	10 mA		
General Specifications						
Storage Memory	99 tests, supplied with DataView® software for download and reporting					

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com



Automatic Storage of Test Results	Yes	
Battery	Rechargeable NIMH battery pack 6V, 8.5Ah.	
Battery Life	10 A	≥ 850 tests with a duty cycle of 5 seconds on and 25s off
	1 A	≥ 3500 tests with a duty cycle of 5 seconds on and 25s off
	100 mA	≥ 4500 tests with a duty cycle of 5 seconds on and 25s off
	10 mA	≥ 5000 tests with a duty cycle of 5 seconds on and 25s off
	In standby mode	Battery life 4 to 6 months
Dimensions (L x W x H)	10.70 x 9.76 x 7.18" (272 x 248 x 182 mm)	
Weight	10 lbs (4.5 kg)	
Operating Temperature	-10° to +55°C (14° to 131°F) & 10 to 85% RH	
Storage Temperature (without battery)	-40° to +70°C (-40° to 158°F) & 10 to 90% RH	
Altitude Operating	2000 m	
IP Rating	IP 54 per IEC 60529 cover closed	
Safety	IEC/EN 61010-1 category III 50V, Pollution Degree 2 <input type="checkbox"/>	

For more details, download the datasheet or user manual at www.aemc.com

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • www.aemc.com
customerservice@aemc.com • techsupport@aemc.com

