



## Digital Multimeter Model 5217

Cat. #2154.09

**TRMS, 6000-count, NCV, V, A, AC/DC, Ohm, T, Frequency, Auto Hold**

Measures voltage (AC and DC), resistance, capacitance, temperature, and frequency. Performs continuity checks and diode testing (including forward bias voltage). Features non-electrical contact testing (NCV) function for detecting live electrical circuits. Includes Auto Range mode and Data HOLD function. Rated to 600V CAT III.

Cat.#2154.09

Counts	6000
Voltage AC/DC	750VAC/1000VDC
Current AC/DC	10AAC/DC
Bandwidth AC	1kHz
Resistance	60MΩ
Frequency	1kHz
Capacitance	100mF
Continuity	<50Ω
Non-Contact Voltage	>90V
Temperature (K-type TC):	-67° to 2192°F
Diode Test	Yes
VLowZ	Yes
Duty Cycle	Yes
ΔREL	Yes
MIN/MAX/AVG/PEAK	MIN/MAX
Flashlight	Yes
Display	Digital with backlighting
Dimensions (HxWxD)	6.7 x 3.1 x 2" (170 x 80 x 50mm)
Weight	11.2oz (320g)
Power Source	2 x1.5V AA
Battery Life	>500 hours

For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)

[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

<b>Operating Temperature</b>	-4° to 120°F (-20° to 49°C)
<b>Storage Temperature</b>	-22° to 130°F (-30° to 54°C)
<b>Pollution Degree</b>	2
<b>Ingress Protection (IP)</b>	IP54
<b>EMC</b>	EN 61326-1, EN 61326-2-2
<b>Safety Compliance</b>	IEC61010-1, IEC61010-2-033, 600V CAT III



For more details, download the datasheet or user manual at [www.aemc.com](http://www.aemc.com)

15 Faraday Drive • Dover, NH 03820 USA • (800) 343-1391 • (603) 749-6434 • [www.aemc.com](http://www.aemc.com)  
[customerservice@aemc.com](mailto:customerservice@aemc.com) • [techsupport@aemc.com](mailto:techsupport@aemc.com)

